


Part no. AL-1642-86231




12-24 V, ECE approval (Reg. 4)

Specifications

| | |
|--------------------------------------|-------|
| Voltage range (V), nominal | 12-24 |
| Voltage range (V), functional | 10-32 |
| Power consumption (W) | |
| Load capacity | |
| Temperature range (°C) | |
| Brightness | |
| Brightness (raw lm) | |
| Brightness (effective lm) | |
| Brightness (cd) | |
| Brightness (lx) | |
| Performance class | |
| Beam pattern/lens | |
| Beam angle [°] | |
| Colour Temperature (K) | |
| Others | |
| Ingress protection | |
| Resistivity | |
| Standards | |
| Electromagnetic Compatibility | ja |
| Transient spike protection | |

Part no. AL-1642-86231

Dimensions



Mounting

| | |
|---------------------------------------|--------------|
| Mounting type | Flachmontage |
| Installation dimensions/diameter [mm] | |
| Installation depth [mm] | |
| Connector | Kabel |
| Mating connector | |
| Reverse polarity protection | 1 |

Part no. AL-1642-86231

Others

| | |
|---------------------------|---------|
| Material (Housing) | |
| Material (Diffusing lens) | |
| Color (Housing) | Schwarz |
| Color (Mount) | |
| Color (Diffusing lens) | Klar |

Beam pattern

Variants

| | |
|---------------|--|
| AL-1642-86231 | 12-24 V, ECE-Straßenzulassung (Reg. 4) |
|---------------|--|

Accessories