

**Part no. AS-1194-90496**



6 modules, 12-24 V, 3,960 lm, flood

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	
<b>Power consumption (W)</b>	144
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	3960
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	über 3000 lm eff.
<b>Beam pattern/lens</b>	Geländeausleuchtung
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Others</b>	
<b>Ingress protection</b>	
<b>Resistivity</b>	

Dimensions

Mounting

Mounting type	Spez. Montagehalter
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	1

**Part no. AS-1194-90496**

## Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	

## Variants

AS-1194-90496	6 Module, 12-24 V, 3960 lm, Geländeausleuchtung
AS-1276-48451	6 Module, 12-24 V, 3960 lm, Fahrlicht

## Accessories