

**Part no. AS-1195-90494**



4 modules, 12-24 V, 2,640 lm, flood

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	
<b>Power consumption (W)</b>	96
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	2640
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	1000 bis 3000 lm eff.
<b>Beam pattern/lens</b>	Geländeausleuchtung
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Others</b>	
<b>Ingress protection</b>	IP67
<b>Resistivity</b>	
<b>Standards</b>	
<b>Electromagnetic Compatibility</b>	ECE (Reg. 10), SAE (J1113)
<b>Transient spike protection</b>	

Dimensions

Mounting

Mounting type	Spez. Montagehalter
Installation dimensions/diameter [mm]	102,87 mm x 727,71 mm
Installation depth [mm]	93,22
Connector	
Mating connector	
Reverse polarity protection	1

Part no. **AS-1195-90494**

**Others**

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	

**Beam pattern**

**Variants**

AS-1195-90494	4 Module, 12-24 V, 2640 lm, Geländeausleuchtung
---------------	---

**Accessories**