

Part no. AS-1196-90492



2 modules, 12 V, 1,320 lm, flood

Specifications

Voltage range (V), nominal	12
Voltage range (V), functional	
Power consumption (W)	48
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	1320
Brightness (cd)	
Brightness (lx)	
Performance class	1000 bis 3000 lm eff.
Beam pattern/lens	Geländeausleuchtung
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	
Standards	
Electromagnetic Compatibility	ECE (Reg. 10), SAE (J1113)
Transient spike protection	

Part no. AS-1196-90492

Dimensions

Mounting

Mounting type	Spez. Montagehalter
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	1

Part no. AS-1196-90492

Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	

Beam pattern

Variants

AS-1196-90492	2 Module, 12 V, 1320 lm, Geländeausleuchtung
---------------	--

Accessories