

# LED-Arbeitsscheinwerfer Modell 880 XD

**Part no. AS-1197-88012**



12-24 V, 700 lm, flood

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	9-32
<b>Power consumption (W)</b>	15,5-16,8
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	-40 bis 65
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	1680
<b>Brightness (effective lm)</b>	900
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	bis 1000 lm eff.
<b>Beam pattern/lens</b>	Geländeausleuchtung
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	5000
<b>Others</b>	
<b>Ingress protection</b>	IP67
<b>Resistivity</b>	

## Dimensions

## Mounting

<b>Mounting type</b>	Universalhalterung, 5/16"-18x1"
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	Deutsch-Stecker (DT04-2P)
<b>Mating connector</b>	Deutsch-Stecker (DT06-2S)
<b>Reverse polarity protection</b>	1
<b>Black wire</b>	Masse
<b>Red wire</b>	Arbeitsscheinwerfer

# LED-Arbeitsscheinwerfer Modell 880 XD

**Part no. AS-1197-88012**

## Others

<b>Material (Housing)</b>	Polycarbonat
<b>Material (Diffusing lens)</b>	Polycarbonat
<b>Color (Housing)</b>	Schwarz
<b>Color (Mount)</b>	
<b>Color (Diffusing lens)</b>	Weiß

## Variants

<b>AS-1197-88012</b>	12-24 V, 700 lm, Geländeausleuchtung
<b>AS-1198-88012</b>	12-24 V, 700 lm, Nahfeldausleuchtung
<b>AS-1199-88012</b>	12-24 V, 700 lm, Spot
<b>AS-1262-03321</b>	12-24 V, 700 lm, Nahfeldausleuchtung, mit Schalter

## Accessories