

Part no. AS-1276-48451



6 modules, 12-24 V, 3,960 lm, driving beam

Specifications

| | |
|--------------------------------------|---------------------|
| Voltage range (V), nominal | 12-24 |
| Voltage range (V), functional | |
| Power consumption (W) | 144 |
| Load capacity | |
| Temperature range (°C) | -40 bis 65 |
| Brightness | |
| Brightness (raw lm) | |
| Brightness (effective lm) | 3960 |
| Brightness (cd) | |
| Brightness (lx) | |
| Performance class | über 3000 lm eff. |
| Beam pattern/lens | Geländeausleuchtung |
| Beam angle [°] | |
| Colour Temperature (K) | 5000 |
| Others | |
| Ingress protection | IP67 |
| Resistivity | |

Dimensions

Mounting

| | |
|--|------------------------|
| Mounting type | Spez. Montagehalter |
| Installation dimensions/diameter [mm] | 102,87 mm x 1043,18 mm |
| Installation depth [mm] | 73,15 |
| Connector | Kabel |
| Mating connector | |
| Reverse polarity protection | 1 |
| Black wire | Masse |
| Red wire | Fahrlicht |

Part no. AS-1276-48451

Others

| | |
|---------------------------|--------------|
| Material (Housing) | Aluminium |
| Material (Diffusing lens) | Polycarbonat |
| Color (Housing) | Schwarz |
| Color (Mount) | |
| Color (Diffusing lens) | Weiß |

Variants

| | |
|---------------|---|
| AS-1194-90496 | 6 Module, 12-24 V, 3960 lm, Geländeausleuchtung |
| AS-1276-48451 | 6 Module, 12-24 V, 3960 lm, Fahrlicht |

Accessories