

# LED-Arbeitsscheinwerfer Modell 4416

**Part no. AS-1567-44131**



12-24 V, 1350 lm, spot, with handle and switch

## Specifications

<b>Voltage range (V), nominal</b>	12-24
<b>Voltage range (V), functional</b>	10-32
<b>Power consumption (W)</b>	26,4
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	2450
<b>Brightness (effective lm)</b>	1350
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	1000 bis 3000 lm eff.
<b>Beam pattern/lens</b>	Spot
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	5000
<b>Others</b>	
<b>Ingress protection</b>	
<b>Resistivity</b>	
<b>Standards</b>	
<b>Electromagnetic Compatibility</b>	
<b>Transient spike protection</b>	

## Dimensions

## Mounting

<b>Mounting type</b>	Handgriff
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	Bordspannungsstecker
<b>Mating connector</b>	
<b>Reverse polarity protection</b>	1
<b>Black wire</b>	Masse
<b>Red wire</b>	Arbeitsscheinwerfer

**Part no. AS-1567-44131**

## Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Polycarbonat
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

## Beam pattern

## Variants

AS-1567-44131	12-24 V, Spot, mit Handgriff und Schalter
---------------	---

## Accessories