

**Part no. BL-1463-37524**



24 V, white

## Specifications

<b>Voltage range (V), nominal</b>	24
<b>Voltage range (V), functional</b>	
<b>Power consumption (W)</b>	4,8
<b>Load capacity</b>	
<b>Temperature range (°C)</b>	-30 bis 50
<b>Brightness</b>	
<b>Brightness (raw lm)</b>	
<b>Brightness (effective lm)</b>	SAE Class I
<b>Brightness (cd)</b>	
<b>Brightness (lx)</b>	
<b>Performance class</b>	
<b>Beam pattern/lens</b>	
<b>Beam angle [°]</b>	
<b>Colour Temperature (K)</b>	
<b>Frequency, revolutions (Hz, rpm, fpm)</b>	9 verschiedene Blitzmuster
<b>Others</b>	
<b>Ingress protection</b>	
<b>Resistivity</b>	
<b>Standards</b>	SAE (J845)
<b>Electromagnetic Compatibility</b>	ja
<b>Transient spike protection</b>	

## Dimensions

## Mounting

<b>Mounting type</b>	Flachmontage, 2 Schrauben
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	Kabel
<b>Mating connector</b>	
<b>Reverse polarity protection</b>	1
<b>Socket</b>	
<b>Red wire</b>	Blitzleuchte
<b>Yellow wire</b>	Moduswahl
<b>Green wire</b>	Masse
<b>Blue wire</b>	Synchronisierung

**Part no. BL-1463-37524**

## Others

Material (Housing)	Aluminium
Material (Diffusing lens)	Acryl
Color (Housing)	Schwarz
Color (Mount)	
Color (Diffusing lens)	Klar

## Beam pattern

## Variants

BL-1463-37524	24 V, weiß
---------------	------------

## Accessories