

Part no. BL-2164-37521



12-24 V, blue

Specifications

| | |
|--------------------------------------|------------|
| Voltage range (V), nominal | 12-24 |
| Voltage range (V), functional | 9-32 |
| Power consumption (W) | 5,1 |
| Load capacity | |
| Temperature range (°C) | -40 bis 65 |
| Brightness | SAE Kl. I |
| Brightness (raw lm) | |
| Brightness (effective lm) | |
| Brightness (cd) | |
| Brightness (lx) | |
| Performance class | |
| Beam pattern/lens | |
| Beam angle [°] | |
| Colour Temperature (K) | |
| Others | |
| Ingress protection | IP67 |
| Resistivity | |

Dimensions

Mounting

| | |
|--|------------------|
| Mounting type | Flachmontage |
| Installation dimensions/diameter [mm] | |
| Installation depth [mm] | |
| Connector | Kabel |
| Mating connector | |
| Reverse polarity protection | 1 |
| Black wire | Masse |
| Red wire | Blitzleuchte |
| Yellow wire | Synchronisierung |
| Blue wire | Moduswahl |

Part no. BL-2164-37521

Others

| | |
|----------------------------------|--------------|
| Material (Housing) | Polycarbonat |
| Material (Diffusing lens) | Polycarbonat |
| Color (Housing) | Schwarz |
| Color (Mount) | |
| Color (Diffusing lens) | Klar |

Variants

| | |
|----------------------|-----------------|
| BL-2162-37521 | 12-24 V, weiß |
| BL-2163-37521 | 12-24 V, orange |
| BL-2164-37521 | 12-24 V, blau |
| BL-2165-37521 | 12-24 V, rot |
| BL-2166-37521 | 12-24 V, grün |

Accessories