

# LED-Fahrscheinwerfer Modell 8800 Evolution 2

Part no. FS-1717-88313



12-24 V, low beam, ECE road approval (Reg. 112),  
black bezel

## Specifications

Voltage range (V), nominal	12-24
Voltage range (V), functional	9-32
Power consumption (W)	25,2-24,0
Load capacity	
Temperature range (°C)	-40 bis 65
Brightness	
Brightness (raw lm)	2830
Brightness (effective lm)	782
Brightness (cd)	29800
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	5000
Others	
Ingress protection	IP69K
Resistivity	

## Dimensions

## Mounting

<b>Mounting type</b>	Einbau
<b>Installation dimensions/diameter [mm]</b>	
<b>Installation depth [mm]</b>	
<b>Connector</b>	AMP (172615-2, H4-Stecker)
<b>Mating connector</b>	AMP (172796-1)
<b>Reverse polarity protection</b>	1
<b>Black wire</b>	Masse
<b>White wire</b>	Abblendlicht

# LED-Fahrscheinwerfer Modell 8800 Evolution 2

**Part no. FS-1717-88313**

## Others

<b>Material (Housing)</b>	Aluminium
<b>Material (Diffusing lens)</b>	Polycarbonat
<b>Color (Housing)</b>	Schwarz
<b>Color (Mount)</b>	Schwarz
<b>Color (Diffusing lens)</b>	Klar

## Variants

<b>FS-1717-88313</b>	12-24 V, Abblendlicht, ECE-Straßenzulassung (Reg. 112), schwarze Einfassung
<b>FS-1718-88314</b>	12-24 V, Abblendlicht, ECE-Straßenzulassung (Reg. 112), verchromte Einfassung
<b>FS-1719-88323</b>	12-24 V, Fernlicht, ECE-Straßenzulassung (Reg. 112), schwarze Einfassung
<b>FS-1720-88324</b>	12-24 V, Fernlicht, ECE-Straßenzulassung (Reg. 112), chrome Einfassung

## Accessories