

Part no. RM-123-15202



6.3 cm diameter (2.5 in.), AMPS, 1.5 in. ball (size C) - RAP-202U

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Part no. RM-123-15202

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-104-15202	6,35 cm (2,5 Zoll), AMPS + 120°-Bohrungen, 1,5-Zoll-Kugel (Größe C) RAM-202U
RM-123-15202	6,3 cm Durchmesser (2,5 Zoll), AMPS, 1,5-Zoll-Kugel (Größe C) RAP-202U
RM-140-15202	6,35 cm, 1,5-Zoll-Kugel (Größe C), verstärkt mit Stahl-Bolzen RAM-202U-IN1

Accessories