

Part no. RM-229-15247



12.5 cm (5 in.), 1.5 in. ball (size C)

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Part no. RM-229-15247

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Part no. RM-229-15247

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-204-15247	Spannweite 6,35 cm (2,5 Zoll), 1,5-Zoll-Kugel (Größe C) RAM-247U-25
RM-205-15247	Spannweite 7,6 cm (3 Zoll), 1,5-Zoll-Kugel (Größe C) RAM-247U-3
RM-206-15247	Spannweite 10 cm (4 Zoll), 1,5-Zoll-Kugel (Größe C) RAM-247U-4
RM-229-15247	12,5 cm (5 v), 1,5-Zoll-Kugel (Größe C) RAM-247U-5

Accessories