

Tough-Claw™ Klammerbasis, 1 Zoll

Part no. RM-300-104



For rail diameter 1,6-3,8 cm (0,625-1,5 in.) or
edges up to 2,9 cm (1,14 in.), 1 in. ball (size B) -
RAP-B-400U

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Page 1/3 19.09.2024

Part no. RM-300-10400

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Tough-Claw™ Klammerbasis, 1 Zoll

Part no. RM-300-10400

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-300-10400	Für Rohrdurchmesser 1,6-3,8 cm (0,625-1,5 Zoll) oder Kanten bis 2,9 cm (1,14 Zoll), 1-Zoll-Kugel (Größe B) RAP-B-400U
RM-301-10401	Für Rohrdurchmesser 2,5-5,6 cm (1-2,25 Zoll) oder Kanten bis 5,7 cm (2,2 Zoll), 1-Zoll-Kugel (Größe B) RAP-B-401U
RM-302-10404	Für Rohrdurchmesser 2,5-4,75 cm (1-1,875 Zoll) oder Kanten bis 4 cm (1,6 Zoll), 1-Zoll-Kugel (Größe B) RAP-B-404U

Accessories

RM-501-10201	Verbindungsstück, 1 Zoll 7,6 cm (3 Zoll), für 1-Zoll-Kugel (Größe B) RAM-B-201U
---------------------	---