

Tough-Claw™ Klammerbasis, 1,5 Zoll

Part no. **RM-306-154**



For rail diameter 1,6-3,8 cm (0,625-1,5 in.) or edges up to 2,9 cm (1,14 in.), 1,5 in. ball (size C)

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Part no. RM-306-15400

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Tough-Claw™ Klammerbasis, 1,5 Zoll

Part no. RM-306-15400

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-306-15400	Für Rohrdurchmesser 1,6-3,8 cm (0,625-1,5 Zoll) oder Kanten bis 2,9 cm (1,14 Zoll), 1,5-Zoll-Kugel (Größe C) RAP-400U
RM-307-15401	Für Rohrdurchmesser 2,5-5,6 cm (1-2,25 Zoll) oder Kanten bis 5,7 cm (2,2 Zoll), 1,5-Zoll-Kugel (Größe C) RAP-401U
RM-308-15404	Für Rohrdurchmesser 2,5-4,75 cm (1-1,875 Zoll) oder Kanten bis 4 cm (1,6 Zoll), 1,5-Zoll-Kugel (Größe C) RAP-404U

Accessories