

Part no. RM-535-0582



15.2 cm (6 in.), 1/2 in. male NPT thread

Specifications

Voltage range (V), nominal	
Voltage range (V), functional	
Power consumption (W)	
Load capacity	
Temperature range (°C)	
Brightness	
Brightness (raw lm)	
Brightness (effective lm)	
Brightness (cd)	
Brightness (lx)	
Performance class	
Beam pattern/lens	
Beam angle [°]	
Colour Temperature (K)	
Others	
Ingress protection	
Resistivity	

Part no. RM-535-05820

Dimensions

Mounting

Mounting type	
Installation dimensions/diameter [mm]	
Installation depth [mm]	
Connector	
Mating connector	
Reverse polarity protection	0

Part no. RM-535-05820

Others

Material (Housing)	
Material (Diffusing lens)	
Color (Housing)	
Color (Mount)	
Color (Diffusing lens)	

Variants

RM-513-05821	30,5 cm (12 Zoll), 1/2-Zoll-NPT-Gewinde (männl.) RAM-PA8212
RM-514-05821	45,7 cm (18 Zoll), 1/2-Zoll-NPT-Gewinde (männl.) RAM-PA8218
RM-515-05821	61 cm (24 Zoll), 1/2-Zoll-NPT-Gewinde (männl.) RAM-PA8224
RM-534-05820	22,9 cm (9 Zoll), 1/2-Zoll-NPT-Gewinde (männl.) RAM-PA8209
RM-535-05820	15,2 cm (6 Zoll), 1/2-Zoll-NPT-Gewinde (männl.) RAM-PA8206

Accessories